




YC-650CL

Touch control
Intelligent Control & Constant Temperature
Multiple Alarms Bring More Security



Temp. Uniformity




Pulling down to 5°C



Temp. recovery after door opened for 1 min

*Typical freezer data based on internal testing with freezer set point at 5°C and ambient temperature at 25°C.

Features



Adjustable shelves' heights



ENERGY STAR certificate



Hydrocarbon refrigerant
Environment-friendly natural gas



CE certificate





Touch screen
7"LCD touch screen



Alarms system
Multiple alarm functions

Structure





2~8°C Pharmacy Refrigerator

Model	YC-650CL	
Capacity	650L/22.95Cu.Ft	
Internal Size (W*D*H) mm	605×725×1515/23.82*28.54*59.65	
External Size (W*D*H) mm	715*890*1985/28.15*35.04*78.15	
Package Size (W*D*H) mm	773*947*2154/30.43*37.28*84.8	
NW/GW (kgs)	157/185	
Performance		
Temperature Range	2~8°C	
Ambient Temperature	16~32°C	
Cooling Performance	5°C	
Climate Class	N	
Controller	Microprocessor	
Display	7"HD IntelligentTouch Screen	
Refrigeration		
Compressor	1pc	
Cooling Method	Air Cooling	
Defrost Mode	Automatical	
Refrigerant	R290	
Insulation Thickness(mm)	D:55, L/R:55, B:55, U/D:55/62	
Construction		
External Material	PCM	
Inner Material	Stainless Steel	
Shelves	5	
Access Test Port	1pc. Ø 23 mm	
Casters	4(2 brakes)	
Data Logging/ Interval /Recording Time	USB/Record every 5 minutes/10 years	
Interface	Remote Alarm Contact, RS485	
Backup Battery	Yes	
Alarms		
Temperature	High/Low Temperature, High Ambient Temperature, Condenser High Temperature Alarm	
Electrical	Power Failure, Low Battery, Battery Power Detection Failure	
System	Sensor Error, Data Communication Failure, Door Ajar	
Electrical		
Power Supply(V/Hz)	110V/60Hz	220-240V;50/60Hz
Rated Current(A)	5.77A	3.06A